

englide

noise.zero
n.zero



	n.zero classic 80	n.zero classic 120	n.zero 120
Dimension:	80x80x25 mm	120x120x25	120x120x25
Weight:	77 g	122 g	122 g
Voltage:	6.5 ~ 13.8 V	6.5 ~ 13.8 V	6.5 ~ 13.8 V
Operation Voltage:	12 V	12 V	12 V
Rotation Speed:	1500 RPM (+- 10%)	980 RPM (+- 10%)	980 RPM (+- 10%)
Noise Level:	17 dBA	17 dBA	17 dBA
Airflow:	19.2 CFM	36 CFM	36 CFM
Bearing:	Sleeve for low RPM	Sleeve for low RPM	Sleeve for low RPM
Warranty:	3 Year Warranty	3 Year Warranty	3 Year Warranty
Cable:	40 cm, 3 - 4 pin	40 cm, 3 - 4 pin	40 cm, 3 - 4 pin
Extra:	Noiseless Cooling	Noiseless Cooling	Noiseless Cooling Semi Transparent Material Anti-Vibration Silicone Mounts

Web: www.englide.com
E-mail: info@englide.com

About Englide:

The main profile of Englide is cooling, in which the founders have close to 10 years of experience. Having regard to the market claims, Englide - with the priority of efficiency, performance and silence - has launched two types of own-designed fans. Both have designed for low RPM and low noise operation.

" Our main target is a totally noiseless case fan. If you just turn down the RPM only, you won't be able to reach real noiseless and efficiency solution. We think a fan can be the best if every parts are optimized for the low RPM operation. The bearing, the motor, the blades, the frame are made for low RPM and low noise. Small pieces make the whole thing perfect. We have close to 10 year experience at cooler business, we know what endusers and partners need. Noiseless fan, design and good price. "

www.englide.com